
INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1YB.04A

removed by abrasive blasting, sanding, or grinding.

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Primary irritant.

SKIN: May irritate skin.

INHALATION: With poor ventilation, vapor or spray mist may irritate respiratory mucous membranes, causing headache & nausea.

INGESTION: N/A

ROUTE(S) OF EXPOSURE

Exposure may be inhalation and/or skin or eye contact, depending on conditions of use.

CARCINOGENICITY

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

CHRONIC EFFECTS:

None recognized.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

SKIN CONTACT: Remove from skin with soap and water. Remove drenched clothing. If irritation persists, consult a physician.

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air. If necessary, restore breathing; in this case contact physician at once.

INGESTION: If victim is conscious, give 2 glasses of water to dilute. Do not induce vomiting. Consult physician or poison control center at once.

NOTE TO PHYSICIAN:

Not Applicable.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification : N/A

Flashpoint : N/A

Explosion Level : Low - .9

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1YB.04A

High - 24.6

EXTINGUISHING MEDIA

Use extinguishing media appropriate for surrounding fire. After water evaporates, remaining material will burn; use CO₂, dry chemical or foam (National Fire Protection Association Class B extinguisher).

FIRE-FIGHTING PROCEDURES AND EQUIPMENT

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat; use water spray to cool. Product in open containers may spatter when the temperature exceeds boiling point of water.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Ventilate as described in Section 8. Avoid unnecessary skin contact. Stop and/or contain spill if it can be done safely. Avoid discharge into drains, sewers or waterways.

CLEAN-UP

Collect by absorption, shovel and/or wet moping.

SECTION 7 - HANDLING AND STORAGE

HANDLING

Transfer only to approved containers with complete & appropriate labeling. Do not take internally. Keep out of the reach of children.

STORAGE

Do not store above 120 Degrees F. Close container after each use.

SPECIAL COMMENTS

Do not take internally. Wash with soap and water before eating, drinking, smoking or using toilet. Avoid FREEZING this product.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to chemicals in Section 2 is maintained below applicable exposure limits.

RESPIRATORY PROTECTION

Where exposures are below the PEL, no respiratory protection is

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1YB.04A

SECTION 12 - ECOLOGICAL INFORMATION

No data at this time.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : N/A
DOT PACKAGING GROUP : N/A
DOT LABEL : NONE
DOT SHIPPING NAME : PAINT
DOT PLACARD : NONE
UN/NA NUMBER : NONE

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

DIETHYLENE GLYCOL MONOBUTYL ETHER

CAS# 112-34-5 PCT BY WT: 4.1570

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 12/15/2005
Last Revision Date : 08/29/2005
MSDS Prepared for :

INSL-X PRODUCTS CORPORATION
MATERIAL SAFETY DATA SHEET

1YB.04A

MSDS Last Prepared : NONE
HMIS Rating: Health- 1 Flammability- 0
 Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m3 or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.

□