

-----  
SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION  
-----

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT ID . . . . . : 1YB.1B  
PRODUCT CLASS . . . . . : CROSSLINKER  
TRADE NAME . . . . . : PROFESSIONAL ACRY URETHANE-FLOOR FIN "B"  
FORMULA ID . . . . . : 370-250B  
MSDS PREPARATION DATE . . . . . : 12/15/2005

MANUFACTURER IDENTIFICATION:

NAME . . . . . : INSL-X PRODUCTS CORPORATION  
ADDRESS . . . . . : 308 OLD COUNTY ROAD  
                                    EDGEWATER                                    FL 32132

TELEPHONE . . . . . : 386-428-6461  
EMERGENCY CONTACT . . . . . : CHEMTREC  
EMERGENCY TELEPHONE . . . . . : (800) 424-9300

-----  
SECTION 2 - COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS  
-----

1  
CAS# 64265-57-2  
POLYFUNCTIONAL AZIRIDINE  
PCT BY WT: 75 - 100  
EXPOSURE LIMIT:  
LD50: Oral (Rat)- 3038 mg/kg  
CA PROPOSITION 65: Yes  
OTHER LIMITS:  
Mutagen

\*\*\*\*\*  
          This product contains one or more reported mutagens or suspected  
mutagens.  
\*\*\*\*\*  
          This product contains no reported carcinogens or suspected carcinogens  
according to the information provided in Section 3 of this MSDS.  
\*\*\*\*\*

-----  
SECTION 3 - HAZARDS IDENTIFICATION  
-----

EFFECTS OF OVEREXPOSURE

EYES: Corrosive to eyes; causes eye burns.  
SKIN: May cause skin defatting with prolonged exposure. Exposure may  
cause skin irritation. Prolonged or repeated exposure may dry  
the skin.  
INGESTION: Harmful if swallowed.  
INHALATION: Breathing mists may cause lung damage and/or allergic  
reaction.  
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE  
Sensitizer for allergic persons.  
PRIMARY ROUTE(S) OF ENTRY  
Dermal, eye contact, inhalation.

-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET

1YB.1B

-----  
CARCINOGENICITY

If applicable, refer to Section 2.

NOTES TO PHYSICIAN

Medical personnel should evaluate persons with chronic pulmonary disease before those workers handle this product.

CHRONIC EFFECTS:

None recognized.

-----  
SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT: Flush at once with large amounts of lukewarm water for at least 15 minutes and get medical attention.

SKIN CONTACT: Immediately remove contaminated clothing, wipe excess from skin and flush with clean water for at least 15 minutes. Wash affected area with soap and water. Get medical attention if persistent irritation and/or a skin rash, appears. Do not reuse clothing until thoroughly cleaned.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

INGESTION: DO NOT INDUCE VOMITING. Keep person quiet. Get medical attention.

NOTES TO PHYSICIAN

Medical personnel should evaluate persons with chronic pulmonary disease before those workers handle this product.

-----  
SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification . . . . .: OSHA Combustible Liquid-Class IIIB  
DOT Not Regulated

Flashpoint . . . . .: 205.0 øF

Explosion Level . . . . .: Low - -N/A  
High - -N/A

EXTINGUISHING MEDIA

Water spray, dry chemical, carbon dioxide (CO2), alcohol foam

SPECIAL FIRE-FIGHTING PROCEDURES

Do not enter fire areas without proper protection. Fight fire from a protected location. Heat may increase temperature and build pressure in closed containers. Spreading fire may increase the risk of injuries. Water may be used to cool closed containers to prevent pressure build-up.

---

INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET

---

1YB.1B

---

UNUSUAL FIRE AND EXPLOSION HAZARDS

This product is normally stable, but can become unstable at elevated temperatures and pressures, or may react with water with some release of energy, but not violently.

---

SECTION 6 - ACCIDENTAL RELEASE MEASURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition (flame, hot surfaces and sources of electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. For large spills, use water spray to disperse vapors and dilute spill to a nonflammable mixture. Prevent runoff from entering drains, sewers, or streams.

CLEAN-UP

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

---

SECTION 7 - HANDLING AND STORAGE

---

PRECAUTIONS TO BE TAKEN IN HANDLING

WARNING: Avoid contact. Very irritating to eyes. Contact with skin may be harmful. Mist generated from spray application may be harmful if inhaled. To protect yourself you must wear safety goggles, impervious gloves, and protective clothes while handling this product. You must wear a respirator during spray operations.

STORAGE

Store in tightly closed, properly vented containers in a cool, dry place. Do not puncture containers or expose product to moisture.

SPECIAL COMMENTS

Do not take internally. Wash with soap and water before eating, drinking, smoking or using toilet.

---

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

---

VENTILATION

Provide general dilution or local exhaust ventilation to remove solid airborne particles of overspray during spray application and to remove decomposition products during welding or flame cutting on surfaces coated with this product.

RESPIRATORY PROTECTION

Any person who may be exposed to this product in the form of an aerosol or mist from spray operations shall, at a minimum, wear a NIOSH

-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET

1YB.1B

-----  
approved category 21c respirator, excluding single use or disposable types in accordance with 30 CFR 11.130 Subpart K. The respirator shall be equipped with high efficiency particulate filters for maximum protection unless an air-supplied respirator is selected. Use of this respirator shall be according to OSHA at 29 CFR 1910.134. If a full-face type respirator is selected and worn, the chemical safety goggles requirement is waived during spray operations.

EYE PROTECTION

Chemical safety goggles.

PROTECTIVE GLOVES

Neoprene, Pioneer's Stanzoil or equivalent.

OTHER PROTECTIVE EQUIPMENT

When skin contact is possible, protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn.

HYGIENIC PRACTICES

Remove and wash contaminated clothing before re-use. Discard contaminated shoes. Wash hands with soap and water. Emergency eye wash wash fountains and safety showers should be available in the immediate vicinity of any potential exposures.

-----  
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

-----

Physical State . . . . .	:	LIQUID		
Vapor Pressure . . . . .	:	-N/A		
Vapor Density . . . . .	:	-N/A		
Boiling Point Range . . . . .	:	Lower - -N/A	øF	
		Higher - -N/A	øF	
Specific Gravity . . . . .	:	1.069		
Weight per Volume . . . . .	:		8.9000	LB/GL
VOC - Total (lbs./gal). . . . .	:	.000		
Evaporation Rate . . . . .	:	.000	(n-Butyl Acetate = 1)	
Volatile by Weight . . . . .	:	.0000		
Volatile by Volume . . . . .	:	.0000		

-----

SECTION 10 - STABILITY AND REACTIVITY

STABILITY: Stable.

INCOMPATIBILITIES (Materials to Avoid): Acidic materials, anhydrides, and strong oxidizers.

HAZARDOUS POLYMERIZATION: May occur if mixed with acidic materials.

-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET

1YB.1B

-----  
CONDITIONS TO AVOID: Contamination with acidic materials, heat,  
direct sunlight, ultraviolet radiation, strong oxidizing conditions,  
and freezing conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal combustion products including  
carbon dioxide, carbon monoxide, and oxides of nitrogen.

-----  
SECTION 11 - TOXICOLOGICAL INFORMATION

-----  
No data at this time.

-----  
SECTION 12 - ECOLOGICAL INFORMATION

-----  
No data at this time.

-----  
SECTION 13 - DISPOSAL CONSIDERATIONS

-----  
WASTE DISPOSAL

Dispose in accordance with local, state, and federal regulations.  
Incinerate in approved facility. Do not incinerate in closed containers.  
Dilute with clean low viscosity fuel. While discarded product is not a  
hazardous waste under RCRA Regulations (40 CFR 261), untreated product  
should not be released to the environment. Treatment or disposal of  
waste products may be regulated by other jurisdictions.

-----  
SECTION 14 - TRANSPORT INFORMATION

-----  
DOT HAZARD CLASS . . . . . : N/A  
DOT PACKAGING GROUP . . . . . : N/A  
DOT LABEL . . . . . : NONE  
DOT SHIPPING NAME . . . . . : NOT REGULATED  
DOT PLACARD . . . . . : NONE  
UN/NA NUMBER . . . . . : NONE

-----  
SECTION 15 - REGULATORY INFORMATION

-----  
U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic  
Substances Control Act (TSCA) inventory of chemicals or are otherwise  
compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains NONE of the substances subject to the reporting  
requirements of Section 313 of Title III of the Superfund Amendments and  
Reauthorization Act of 1986 and 40 CFR Part 372.

-----  
INSL-X PRODUCTS CORPORATION  
MATERIAL SAFETY DATA SHEET  
-----

1YB.1B  
-----

SECTION 16 - OTHER INFORMATION  
-----

Prepared by . . . . . :  
Date of issue . . . . . : 12/15/2005  
Last Revision Date . . . . . : 11/15/2005  
MSDS Prepared for . . . . . :  
MSDS Last Prepared . . . . . : NONE  
HMIS Rating:           Health- 3           Flammability- 1  
                          Reactivity- 1

\*\*\*\*\*

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200 (g) (4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

\*\*\*\*\*

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m3 or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.

□